

1901

Exposed Sequential Shower Valve with Diverter & Rigid Riser Kit

Product Specification

Product Code:	N2 SQSHXDIV C
Finish:	Chrome
Connection Inlet:	15mm Compression
Inlet Centres:	Adjustable from 136mm – 158mm
Maximum Temperature:	Pre-set 42oC
Pressure Range:	Min 0.3 Bar, Max 5.0 Bar

Additional Information

- Chrome plated to BS EN 248:2002
- Supplied with 2 x 8 l/min. flow regulators
- Adjustable inlet centres mean you can use existing pipework with centres measuring anything between 136mm and 158mm.
- Shower kit with external diverter, shower rose, rigid riser and rub clean handset
- Factory fitted regulators means this is a water saving shower
- Matching taps available



Flow Rates (litres per minute)

System Pressure	0.3bar	0.4bar	1bar	2bar	3bar	4bar	5bar
Through Rose, with Flow Regulators	---	---	3.6	5.5	8	9.9	12.2
Through Rose, without Flow Regulators	2.6	3.2	3.6	5.6	8.3	10.3	13.5
Through Handset (mixed) with Flow Regulators	---	---	3.3	4.9	7.1	8.7	8.7
Through Handset (mixed) without Flow Regulators	2.5	2.9	3.3	5	7.2	8.7	11.3

Technical Advice: For further information please call 0844 7016273 or email customer@bristan.com

Guarantee: 5 years covering manufacturing faults.

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG
 Telephone: 0844 701 6274 Facsimile: 0844 701 6275
 Web Site: www.bristan.com Email: enquire@bristan.com



The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.