



the electric heating company

DIRECT AND INDIRECT UNVENTED STAINLESS STEEL CYLINDERS

DIRECT UNVENTED STAINLESS STEEL CYLINDERS



The following fittings are supplied with our Direct Cylinders:

- Inlet Control Set
- Temperature & Pressure Relief Valve
- 15mm / 22mm Tundish
- Expansion Vessel c/w Wall Mounting Bracket
- 2 x 3kW Immersion Heaters
- Installation & Maintenance Instructions
- Benchmark Logbook

Recommendations based on the guidelines in BS 6700

Hot Water Demand	Number of Bedrooms	Indirect units	Direct units
1 Standard Bath or Shower	Bedsit or 1	120	150
	2 or 3	120	180
	3 or 4	150	210
1 Standard Bath	2 or 3	120	180
	3 or 4	150	210
1 Standard Bath & En-suite	2 or 3	150	210
	3 or 4	150	210
	4 or 5	180	250
2 Standard Baths	2 or 3	180	210
	3 or 4	180	210
	4 or 5	210	250
3 Bathrooms	3 or 4	250	300
	4 or 5	250	300
	5 or 6	300	300

Model No.	CAPACITY (Litres)	HEIGHT (mm)	DIAMETER (mm)	WEIGHT (Kg-EMPTY)	WEIGHT (Kg-FULL)
NDIR90L	90	720	545	17	107
NDIR120L	120	900	545	21	141
NDIR150L	150	1100	545	26	176
NDIR180L	180	1280	545	28	208
NDIR210L	210	1470	545	32	242
NDIR250L	250	1720	545	39	250
NDIR300L	300	1980	545	45	300

INDIRECT UNVENTED STAINLESS STEEL CYLINDERS



The following fittings are supplied with our Indirect Cylinders:

- Inlet Control Set
- Temperature & Pressure Relief Valve
- 15mm / 22mm Tundish
- Expansion Vessel c/w Wall Mounting Bracket
- 1 x 3kW Immersion Heater - On Cylinders 210L & Smaller
- 2 x 3kW Immersion Heaters - On Cylinders 250L & Greater
- Two Port Zone Valve
- Dual Thermostat
- Installation & Maintenance Instructions
- Benchmark Logbook

Note: Slimline Direct & Indirect models available (475mm in Diameter)

25 Year Warranty
on Direct & Indirect Cylinders



Model No.	CAPACITY (Litres)	HEIGHT (mm)	DIAMETER (mm)	WEIGHT (Kg-EMPTY)	WEIGHT (Kg-FULL)
NIND90L	90	720	545	21	109
NIND120L	120	900	545	25	143
NIND150L	150	1100	545	29	177
NIND180L	180	1280	545	33	211
NIND210L	210	1470	545	37	245
NIND250L	250	1720	545	43	291
NIND300L	300	1980	545	50	347