

# BUNDED OIL TANKS

## Secure Storage

Harlequin®  
StorageTanks®

RELIABLE CONTAINERS

### Harlequin Bunded Oil Tanks

The Harlequin range of Bunded Oil Tanks are available from 350 litres, up to 10,000 litre models. Each tank has been designed and manufactured to exceed the most technical, environmental and regulatory requirements. Available as a tank only HQI model, tank and tankpack ITE model, or top outlet ITT model.

### What is a Bunded Oil Tank?

A 'Bunded' oil tank simply consists of a tank within a tank. Oil is stored in the inner tank and the outer tank acts as a failsafe so that in the event of a spillage, excess oil will collect in the outer tank - thus averting a pollution incident and costly environmental clean-up operation.

Bunded oil tanks have been proven to significantly reduce the risk of pollution at oil storage installations. They are a requirement at most commercial, industrial and institutional premises; all installations in the Channel Islands; and, at many domestic installations in the United Kingdom and Republic of Ireland.

### Benefits of a Harlequin Bunded Oil Tank:

- **More Options** - the full range has 14 options of tank size, a tank to suit every installation requirement.
- **Integrally Bunded** - designed to protect the surrounding environment, all tanks are bunded preventing pollution if the internal tank was ever to leak.
- **Non Corrosive** - manufactured from Medium Density Polyethylene (MDPE) your Harlequin tank will not corrode.
- **10 Year Guarantee** - peace of mind that should an issue arise with your tank, Harlequin will be there to help. \*10 year guarantee upon registration with Harlequin.
- **Meets Regulations** - as well as being fully bunded, each tank meets all relevant regulatory requirements.
- **Contents Monitoring** - each model has a 32mm hole suitable for fitting an electronic gauge. Gauge is standard with ITE and ITT models



All tanks are fully bunded and meet all regulatory requirements.

### ABOUT HARLEQUIN MFG

Being one of Europe's largest manufacturers of rotationally moulded plastic tanks, we've been at the forefront of product developments for over 35 years. From our base in Northern Ireland we design, manufacture and deliver our tanks all over the world.

With your Harlequin tank you can be assured you have the best solution for your needs. Our unrivalled reputation for quality is backed up by our 9001, 14001 and 18001 Quality Standard Certifications.

Visit our website to find out about our full range of products:

Fuel/Diesel Tanks | Hot Water Systems | Wastewater Systems  
Water Tanks | Rainwater Harvesting | Bunkers & more.



Tweet us your installation:  
@HarlequinMFG



For the latest product information, give us a call or visit our website:

T 028 9261 1077 E [Info@harlequin-mfg.com](mailto:Info@harlequin-mfg.com)  
[www.harlequin-mfg.com](http://www.harlequin-mfg.com)

Harlequin®  
MANUFACTURING FOR TOMORROW

# Bunded Oil Tanks

The Harlequin range of Bunded Oil Tanks are manufactured to exceed the most demanding technical, environmental and regulatory requirements. Available from 350 litres right up to 10,000 litre models, each tank is CE marked where appropriate with Declarations of Performance available on request.



**350 HQi**  
VERTICAL  
Diameter 980mm  
Height 1,160mm  
Capacity 358 litres  
Weight 45kg



**650 HQi / ITE / ITT**  
SLIMLINE  
Length 1,715mm  
Width 670mm  
Height 1,330mm  
Capacity 673 litres  
Weight 116kg



**1000 HQi / ITE / ITT**  
SLIMLINE  
Length 2,150mm  
Width 690mm  
Height 1,420mm  
Capacity 1,055 litres  
Weight 132kg

OFCERT License no: 0644051004R

OFCERT License no: 0644051005R



**1100 HQi / ITE / ITT**  
SLIMLINE  
Length 1,880mm  
Width 890mm  
Height 1,595mm  
Capacity 1,097 litres  
Weight 132kg



**1200 HQi / ITE / ITT**  
LOW PROFILE  
Length 1,900mm  
Width 1,600mm  
Height 950mm  
Capacity 1,317 litres  
Weight 128kg



**1300 HQi / ITE / ITT**  
SLIMLINE  
Length 2,100mm  
Width 950mm  
Height 1,540mm  
Capacity 1,344 litres  
Weight 168kg

OFCERT License no: 0644010901R

OFCERT License no: 0644031201

OFCERT License no: 0644051006R



**1400 HQi / ITE / ITT**  
HORIZONTAL  
Length 1,900mm  
Width 1,250mm  
Height 1,420mm  
Capacity 1,452 litres  
Weight 135kg



**1450 HQi / ITE / ITT**  
VERTICAL  
Diameter 1,540mm  
Height 1,590mm  
Capacity 1,498 litres  
Weight 112kg



**2000 HQi / ITE / ITT**  
HORIZONTAL  
Length 2,360mm  
Width 1,320mm  
Height 1,415mm  
Capacity 2,092 litres  
Weight 180kg

OFCERT License no: 0644010902R

OFCERT License no: 0644010903R

OFCERT License no: 0644010904R



**2500 HQi / ITE / ITT**  
HORIZONTAL  
Length 2,460mm  
Width 1,435mm  
Height 1,470mm  
Capacity 2,571 litres  
Weight 210kg



**3500 HQi / ITE / ITT**  
HORIZONTAL  
Length 2,450mm  
Width 1,770mm  
Height 1,890mm  
Capacity 3,471 litres  
Weight 265kg



**5400 HQi / ITE / ITT**  
VERTICAL  
Diameter 2,575mm  
Height 2,125mm  
Capacity 5,307 litres  
Weight 325kg

OFCERT License no: 0644051003R

OFCERT License no: 0644031202

OFCERT License no: 0644010318R



**7500 HQi / ITE / ITT**  
VERTICAL  
Length 3,115mm  
Width 2,305mm  
Height 3,020mm  
Capacity 7,697 litres  
Weight 500kg



**10000 ITE / ITT**  
VERTICAL  
Length 3,320mm  
Width 2,510mm  
Height 3,150mm  
Capacity 10,974 litres  
Weight 660kg

Your accredited Harlequin Reseller:

or contact us to find your nearest reseller: 028 9261 1077

**OPTION 1: HQi**  
Bunded Oil Tank only.

Specification:

- Integrally bunded
- Bottom outlet with 1" BSP(F) thread
- 16" lockable access lid
- 4" lockable inspection cap (fill point for 350 model)
- 2" BSP(M) fill point (excludes 350 model)
- 32mm hole with cover for electronic gauge
- Inner tank vent (excludes 350 model)

Additional to specific models:

- Mechanical overfill prevention valve (3500, 5400, 7500 models)

**OPTION 2: ITE**  
Bunded Oil Tank with gauge and bottom outlet kit.

Specification:

- Integrally bunded
- Bottom outlet with 1" BSP(F) thread
- 16" lockable access lid
- 4" lockable inspection cap
- 2" BSP(M) fill point
- 32mm hole with cover for electronic gauge
- Inner tank vent
- Ultrasonic contents gauge
- Bottom outlet fitting kit
- LRC overfill prevention probe

Additional to 3500, 5400, 7500, 10000 models:

- Mechanical overfill prevention valve
- Bund Monitor

**OPTION 3: ITT**  
Bunded Oil Tank with top outlet & gauge.

Specification:

- Integrally bunded
- Tanktop top offtake fitting\*
- 16" lockable access lid
- 4" lockable inspection cap
- 2" BSP(M) fill point
- 32mm hole with cover for electronic gauge
- Inner tank vent
- Ultrasonic contents gauge
- LRC overfill prevention probe

Additional to 3500, 5400, 7500, 10000 models:

- Mechanical overfill prevention valve
- Bund Monitor

\* 5400, 7500, 10000 models fitted with Ecoflex top offtake fitting

Top Outlet



**Please Note:** All tank capacities are brimful. All OFCERT license numbers are for ITE models, ITT OFCERT license numbers are available on the OFTEC website. All information contained herein is understood to be correct at time of publication. Harlequin reserve the right to amend product specification without notice.

For the latest product information, give us a call or visit our website:

T 028 9261 1077 E [Info@harlequin-mfg.com](mailto:Info@harlequin-mfg.com)  
[www.harlequin-mfg.com](http://www.harlequin-mfg.com)